

Attachments / Trencher Specifications

Units US

Trencher, MX112

Trencher, LT112

Trencher, LT113

Trencher, LT213

LT313 (4ft)



General

Operating Weight	570 lb	613 lb	638 lb	725 lb	980 lb
Length	68.2 in	60.7 in	74 in	74 in	89.5 in
Width	30.6 in	36 in	36 in	56 in	56 in
Height	n/a	n/a	n/a	n/a	n/a
Auger Diameter	12 in	12 in	12 in	12 in	13 in
Frame Width (std. equipment)	30.6 in	36 in	36 in	56 in	56 in
Maximum Operating Pressure	3,000 psi	3,000 psi	3,000 psi	3,300 psi	3,300 psi
Side Shift Travel	16.1 in	16.1 in	16.1 in	23.1 in	23.1 in
Side Shift Type	n/a	MANUAL	MANUAL	MANUAL	MANUAL
Chain Tensioning	n/a	GREASE CYLINDER	GREASE CYLINDER	GREASE CYLINDER	GREASE CYLINDER
Chain Options	n/a	MULTIPLE	MULTIPLE	MULTIPLE	MULTIPLE
Flow Range	n/a	9-15 GPM	9-15 GPM	11-18 GPM	15-24 GPM
Auger Clearance	n/a	13.8-15.8 IN	13.8-15.8 IN	13.8-15.8 IN	24.0-27.0 IN
Standard Boom Length	39.4 in	39.4 in	52.5 in	52.5 in	65.5 in
Dig Depth	24 in	24 in	36 in	36 in	48 in
Widths Available Min	4 in	4 in	4 in	4 in	6 in
Widths Available Max	8 in	8 in	8 in	8 in	12 in

Compatible Carriers

Skid-Steer Loaders					
Bobcat A770					■
Bobcat S64					■
Bobcat S66					■
Bobcat S70		■	■		
Bobcat S76					■
Bobcat S450				■	■
Bobcat S550					■
					■

Bobcat S570					
Bobcat S590					■
Bobcat S595					■
Bobcat S650					■
Bobcat S740					■
Bobcat S770					■

Compact Track Loaders

Bobcat T64					■
Bobcat T66					■
Bobcat T76					■
Bobcat T450				■	■
Bobcat T550					■
Bobcat T590					■
Bobcat T595					■
Bobcat T630					■
Bobcat T650					■
Bobcat T740					
Bobcat T770					

Mini Track Loaders

Bobcat MT55		■	■		
Bobcat MT85		■	■		

Compact Excavators

Bobcat E32 M-Series	■				
Bobcat E35 33 HP	■				
Bobcat E35 M-Series	■				
Bobcat E42 R2	■				
Bobcat E50 R2	■				
Bobcat E55	■				

Toolcat™ Work Machine					
Bobcat 5600				■	
Bobcat 5610				■	

Small Articulated Loader					
Bobcat L23		■	■		
Bobcat L28		■	■		

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.